

ZX-DA-04

Paraffin Remover (oil soluble)

General

Oil soluble Paraffin Remover ZX-DA-04 is composed of alkanes without benzene and chlorine and surfactant, which can remove the wax in oil wells. It does not contain benzene, chlorine and heavy metals. Paraffin Remover ZX-DA-04 has emulsifying, wetting, dispersing and other properties. It has outstanding effect on high freezing point wax and gum.

Characteristics

- 1, high efficiency wax removal, fax wax dissolving speed and high wax removal efficiency;
- 2, Simple construction and convenient use;
- 3, It is safe and environmentally friendly without benzene, chlorine and heavy metals;
- 4, It can reduce production costs and improve oil production efficiency;
- 5, Strong adaptability, safety and environmental protection;

Composition

Composed of alkanes without benzene and chlorine and surfactant

Product

Appearance	Generally colorless, light yellow to yellow and can flow freely
pH	Approx. 7-10
Wax prevention rate %	≥20%
Wax dissolution rate (g/min)	≥0.025
Closed Flash point	≥150°C
Condensation point	≤-15°C
Organic chlorine content	0.0%
Carbon dioxide content	0.0%

Note: for general areas, the pour point should not exceed -15°C while for special areas, the pour point should not be higher than the local minimum temperature.

Note: Water soluble paraffin remover is composed of high flash point organic solvent mixture, stabilizer and surfactant.

Application

Usage and dosage

The service life of this product is determined according to the wax deposition degree and wax deposition cycle of the oil well. It is slowly added by intermittent manual dosing. The dosage is determined according to the site situation.

oil soluble Paraffin Remover ZX-DA-04 is mainly used to prevent and remove wax, gum and asphaltene blockage in wellbore, formation and oil pipeline, so as to delay wax deposition time, improve oil fluidity, extend the cycle of wax removal and pump inspection, and improve oil production rate and economic benefits.

if water soluble based paraffin remover is mainly used to remove wax scale in the tubing of oil wells in the oilfield, dredge the tubing and improve oil production.

Packing

Paraffin Remover ZX-DA-04 is generally packed in iron or plastic drums, and can be divided into different specifications of drums with a net weight of 1000kg, 200kg, and 25kg. Packaging can be customized according to customers' requirement. During transportation, it should be loaded and unloaded gently, avoid collisions, and so not invert.

Storage

Paraffin Remover ZX-DA-04 should be stored in a dry, cool and ventilated warehouse, away from fire and heat sources. When handling and using, avoid contact with skin or splashing into eyes. Once in contact, rinse immediately with plenty of water.

Shelf life: 1 year.